Product Bulletin

SulfaTreat[®] 410 HP[™]

SULFATREAT — 410 HP Odor-Control Product safely and irreversibly removes hydrogen sulfide and light mercaptan type odors from any air or gas stream. It is a non-corrosive, non-toxic granular material that selectively treats hydrogen sulfide and light mercaptans (methyl and ethyl) in a batch type process. This high-capacity product is unique in that it reliably and predictably functions in partially to fully humid air.

For convenient disposal, SULFATREAT — 410 HP is easy to handle and environmentally safe in both its un-reacted and reacted forms.

TYPICAL PHYSICAL PROPERTIES

APPLICATIONS

SULFATREAT — 410 HP systems are extremely flexible and can treat all concentrations of hydrogen sulfide to virtually any outlet concentration desired, maintaining treatment during variations encountered in normal operation without operator adjustment. This product is also ideal for treating biogas (digester and landfill), industrial vent gas, and other non-air streams that benefit from its low pressure-drop characteristics.

SULFATREAT — 410 HP can be used in common drum, box, or tank type vessels. Entrained or condensed liquids and solids should be removed in a separator, knockout, or drip pot just prior to entering the vessel(s). SULFATREAT — 410 HP is applied in fixed bed reaction vessels operated, preferably, in down-flow mode (helps prevent accumulation of condensed liquids). Bed depths can range from 18 inches, with good inlet distribution and outlet collection design, up to 40 ft.

Systems can range from single or multiple vessels in parallel flow to lead/lag, or reversible series flow through two vessels where heavy loads of H_2S are encountered. Computer-aided design will specify the appropriate system and bed design, and the process results, such as pressure drop, days to operate, etc.

SulfaTreat

| HANDLING | SULFATREAT — 410 HP product can be kept for an indefinite period of time under normal storage condi- tions without loss of effectiveness. It can be stored outside if protected | from direct weather elements. No special handling or environmental inventory is required because the product is environmentally non- hazardous and non-toxic. |
|------------------------------|---|--|
| PRICE | 2,000-lb super sacks | |
| DISTRIBUTION AND HANDLING | SULFATREAT — 410 HP is available in 2,000-lb super sacks and 50-lb bags from the main warehouse in | St. Louis, Missouri, from stock loca- tions in the U.S.A. and Canada, or from an authorized distributor. |
| PRESSURE-DROP CURVE | SULFATREAT will assist owners and contractors by specifying the appro- priate SULFATREAT — 410 HP system. SULFATREAT offers pre-assembled pack- ages that include blowers, in 25- and 50-cfm flow capacities, ideal for low- flow "wet well" applications. Large systems can use custom designed | SULFATREAT Odor Control Units avail- able for flows ranging from less than 1,000 to more than 6,000 cfm per unit, depending upon specified oper- ating conditions. These low-profile units are specifically designed for low pressure drop and even distrib- ution across the beds. |
| | Pressure-Drop Curve | |

Pressure drop (inches of wat 3 Settled bed 2 --.... . . 1 Loose-packed bed -0 0 10 30 40 50 20 Superficial velocity (fpm)

 \oplus

This information is supplied solely for informational purposes and M-I *iLC* makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.

©2002 M-I LLC All rights reserved. ©SULFATREAT is a registered trademark of M-I LLC IMHP 410 is a trademark of M-I LLC MI-02329 1.5M 7/02 Printed in U.S.A.



A Business Unit of M-I LLC. A Smith/Schlumberger Company 17998 Chesterfield Airport Road, #215 Chesterfield, Missouri 63005 Tel: 636-532-2189 Toll-free: 800-726-7687 Fax: 636-532-2764 E-mail: info@SULFATREAT.com